

DESCRIPTION

OPTICAL PICKUP DEVICE

5 TECHNICAL FIELD

[0001] The present invention relates to a pickup and an optical pickup device that avoids collision of an optical disk.

BACKGROUND ART

10 [0002] A recording and reproducing device, such as a CD (Compact Disk) player/recorder or a DVD (Digital Video (Versatile) Disk) player/recorder, reads information recorded on an optical disk, such as a CD. In reading information, the recording and reproducing device emits a
15 light beam from a light source included in a pickup of the recording and reproducing device onto an information recording surface of the optical disk, and detects a reflected light from the information recording surface.

[0003] The pickup also includes an actuator that drive-
20 controls an objective lens. The objective lens converges the light beam emitted from the light source on the information recording surface. A focal point of the light beam irradiated onto the information recording surface is adjusted according to a distance between the objective lens
25 and the information recording surface.

[0004] To perform such adjustment of the focal point,

the CD player or the like controls the actuator by focus servo control. The actuator is controlled to drive-control the objective lens in a direction of an optical axis of the objective lens so that the light beam can be focused with
5 an optimum focal point onto the information recording surface.

[0005] To irradiate the light beam with the optimum focal point, there is conventionally known a technique that detects a real focal point onto the information recording
10 surface, and controls a position of the objective lens according to a deviation between the real focal point and an optimum focal point.

[0006] However, if the detected real focal point is in error, due to say surface warping of the optical disk, a
15 scratch on the information recording surface or the like, the various problems can occur. For example, the position of the objective lens relative to the optical disk cannot be accurately detected. As a result, the objective lens or the like collides against the information recording surface
20 of the optical lens. It is, therefore, necessary to accurately detect the position of the objective lens and control movement of the objective lens to avoid collision between the objective lens and the information recording surface.

25 [0007] A focus controller disclosed in Patent Document 1 determines whether there is a possibility of collision

between the objective lens and the optical disk. Namely,
the focus controller monitors two factors: a distance
between the objective lens and the optical disk, and a
velocity of the objective lens at which the objective lens
5 approaches the optical disk.

[0008] Patent Document 1: Japanese Patent Application
Laid-Open No. 2002-157758

DISCLOSURE OF INVENTION

10 PROBLEM TO BE SOLVED BY THE INVENTION

[0009] In the conventional technique disclosed in the
Patent Document 1, whether there is a possibility of
collision between the objective lens and the optical disk
by detecting the distance between the objective lens and
15 the optical disk based on a focus error signal; however, a
range in which the distance can be detected is narrower
than a range in which the objective lens is moved. As a
result, the detected distance between the objective lens
and the optical disk is often in error. Furthermore, the
20 objective lens is moved for a considerable distance when
detecting the position of the optical disk performed when
recording or reproducing of information on or from the
optical disk is started. As a result, an error in the
detected distance between the objective lens and the
25 optical disk can be very conspicuous. If the objective
lens performs a collision avoidance operation based on a

wrong distance, the focus servo control cannot be closed.

[0010] The present invention has been achieved to solve
the conventional problems. It is an object of the present
invention to obtain an optical pickup device that can
5 prevent collision between an objective lens and an
information recording surface of an optical disk.

MEANS FOR SOLVING PROBLEM

[0011] To solve the above problems and to achieve the
10 above objects, according to the invention disclosed in
claim 1, an optical pickup device for irradiating a light
from a light source onto an optical recording medium
through an objective lens moved in a focal direction by an
actuator, and for causing a signal detecting unit to
15 receive a return light from the irradiated light, includes
an access limit introducing unit that obtains shape
information on the optical recording medium in a diameter
direction before recording and/or reproducing is performed
on the optical recording medium, and that sets limits to
20 access distances of the objective lens to the optical
recording medium according to a plurality of positions of
the optical recording medium in the diameter direction,
respectively based on the obtained information on the
shape; and a collision avoiding unit that restricts
25 movement of the objective lens in the focal direction by
the actuator based on the plurality of set limits to the

access distances.

[0012] Moreover, according to the invention disclosed in
claim 8, a collision preventing method of preventing
collision between an objective lens moved by an actuator in
5 a focal direction and an optical recording medium onto
which a light is irradiated from a light source, includes a
first step of obtaining shape information on the optical
recording medium in a diameter direction before recording
and/or reproducing is performed on the optical recording
10 medium; a second step of setting limits to access distances
of the objective lens to the optical recording medium
according to a plurality of positions of the optical
recording medium in the diameter direction, respectively
based on the obtained shape information; and a third step
15 of restricting movement of the objective lens in the focal
direction by the actuator based on the plurality of set
limits to the access distances.

BRIEF DESCRIPTION OF DRAWINGS

20 [0013]

Fig. 1 is schematic of a pickup according to a first
embodiment of the present invention.

Fig. 2 is a block diagram of a disk-collision avoiding
device according to the first embodiment.

25 Fig. 3 is a flowchart of an operation procedure for
avoiding collision between an objective lens and an optical

disk.

Fig. 4 is an example of a focus error signal.

Fig. 5 is schematic for explaining the relationship
between focus drive currents and in-focus states calculated
5 by the disk-collision avoiding device.

Fig. 6 is a graph for explaining the method of
calculating thresholds of the focus drive currents.

Fig. 7 is a schematic of a pickup according to a
second embodiment of the present invention.

10 Fig. 8 is a block diagram of a disk-collision avoiding
device according to the second embodiment.

Fig. 9 is a schematic for explaining the relationship
between moving distances of an objective lens and in-focus
states calculated by the disk-collision avoiding device.

15 Fig. 10 is a schematic of a pickup according to a
third embodiment of the present invention.

Fig. 11 is a block diagram of a disk-collision
avoiding device according to the third embodiment.

20 EXPLANATIONS OF LETTERS OR NUMERALS

[0014]

1-3 Disk-collision avoiding device

10 Pickup

15 Signal detecting unit

25 16, 46 Objective-lens driving unit

20 Objective lens holder

	21	Focus coil
	22	Objective lens
	31	Focus driving unit
	32	Drive-current detecting unit
5	34	Radial-position detecting unit
	35	Focus control unit
	36	Threshold calculating unit
	37	Storing unit
	42	Moving-distance calculating unit
10	45	Position sensor
	55	Mechanical stopper
	57	Coil
	58	Stopper unit
	59	Mechanical stopper driving unit
15	70	Optical disk

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0015] Exemplary embodiments of an optical pickup device according to the present invention will be explained hereinafter. The present invention is not limited to the embodiments. Outline and features of the optical pickup device according to the present invention will be explained as the embodiments, and the embodiments of the optical pickup device will be specifically explained.

25 [0016] [Embodiments]

According to the embodiments of the present invention,

a digital signal recording and reproducing device such as a
CD (Compact ~~Dise~~ Disk) player or a CD recorder includes a
pickup device (i.e., an optical pickup device) or the like
as a device that reads information recorded on an optical
5 disk. The pickup device includes an actuator. The
actuator drives an objective lens to control a focus i.e.,
focal point, of a light beam irradiated onto the optical
disk. Furthermore, a disk-collision avoiding device
included in the optical pickup device provides control to
10 avoid collision between a head of an objective lens or the
like employed to record or reproduce information on and
from an optical recording medium (optical disk) and the
optical disk when the information recorded on the optical
disk is reproduced or recorded.

15 [0017] The focal point of the light beam irradiated onto
the optical disk is adjusted according to the distance
between the objective lens and the optical disk. The
objective lens is driven such that the focal point is
optimum.

20 [0018] A focus error signal is a signal indicative of
the distance between the objective lens and the optical
disk. From the focus error signal, the distance between
the objective lens and the optical disk can be detected.
Therefore, by using the focus error signal, the collision
25 between the objective lens and the optical disk can be
avoided.

[0019] Basically, the focus error signal indicates a zero level (to be exact, a zero-crossing point from a maximal point to a minimal point) in an in-focus state in which the focus of the objective lens is on the recording surface. The focus error signal draws an S-curve around the zero level from the maximal point to the minimal point, i.e., a focal point. In addition, the focus error signal exhibits linearity only in a range from the maximal point to the minimal point on one S-curve (which is a range of about ten micrometers from a focal position).

[0020] Meanwhile, the distance between the objective lens and the optical disk is about several hundreds micrometers to two millimeters when the objective lens is the in-focus state. Therefore, the distance between the objective lens and the optical disk that can be recognized by detecting the focus error signal is far smaller than the range in which the objective lens is moved.

[0021] Moreover, to control a collision avoidance operation for avoiding collision between the objective lens and the optical disk (an operation of keeping the objective lens away from the optical disk or the like) according to the distance between the objective lens and the optical disk, the following method is known. A threshold of the focus error signal for the collision avoidance operation is set within a capture range (about ten micrometers) of the focus error signal. However, an operation of detecting the

position of the optical disk performed when reproducing of
information from the optical disk is started is executed by
greatly moving the objective lens. Due to this, when the
reproducing of information from the optical disk is started,
5 the focus error signal often exceeds the threshold for
determining whether to perform the collision avoidance
operation. If the focus error signal exceeds the threshold
for determining whether to perform the collision avoidance
operation, the objective lens performs the collision
10 avoidance operation. As a result, the focus servo control
cannot be closed.

[0022] According to the embodiments of the present
invention, the following measures are taken. The
relationship between information on a position of the
15 objective lens relative to the pickup device (a focal
direction distance) and the focus error signal is obtained
in advance as shape information on the optical disk
(optical recording medium). A plurality of limits to an
access distance (hereinafter, also "access distance
20 limits") of the objective lens to the optical disk are set
according to positions of the optical recording medium in a
diameter direction. The actuator restricts movement of the
objective lens in the focal direction based on the access
distance limits, and the collision between the objective
25 lens and the optical disk is avoided.

[0023] For instance, as the information on the position

of the objective lens relative to the pickup device, a drive current for drive-controlling the movement of the objective lens relative to the pickup is used. The drive current can control a moving distance of the pickup
5 according to a magnitude of the drive current.

[0024] Before recording or reproducing of the information on or from the optical disk, the focus error signal is detected while rotating the optical disk at a predetermined position on a surface of the optical disk.
10 The in-focus state in which the focus of the objective lens is on the recording surface of the optical disk is detected based on the focus error signal. During detection, if a drive current I_1 for moving the objective lens from a neutral position to a position of the in-focus state is
15 measured, the drive current I_1 in the in-focus state can be recognized. Furthermore, the distance between the objective lens and the optical disk in the in-focus state can be calculated from a wavelength of the light beam or the like. A drive current I_{wd} necessary to move the
20 objective lens by the distance can be calculated. It, therefore, indicates that the objective lens collides against the optical disk when the drive current is equal to $(I_1 + I_{wd})$. For this reason, if a threshold (limiter) of the drive current for moving the objective lens is set at the
25 measurement position based on the drive current $(I_1 + I_{wd})$, the collision between the objective lens and the optical

disk can be avoided.

[0025] Thresholds of the drive current (access distance
limits of the objective lens to the optical disk) are
calculated at a plurality of locations on the surface of
5 the optical disk (positions in the diameter direction
different in a radial position from a center), respectively.
Thresholds of the drive current on the entire surface of
the optical disk are calculated based on the relationship
between the positions of the optical disk in the diameter
10 direction on the surface of the optical disk and the
thresholds of the drive current.

[0026] When the information is actually recorded or
reproduced on or from the optical disk, the movement or the
like of the objective lens is controlled based on the
15 thresholds of the drive current calculated in advance to
avoid the collision between the objective lens and the
optical disk if the drive current exceeds the corresponding
threshold.

[0027] In this manner, according to the embodiments, the
20 possible collision between the objective lens and the
optical disk is detected without using the focus error
signal during the recording or reproducing processing on
the optical disk. Due to this, the position of the
objective lens relative to the optical disk can be
25 accurately detected even with a surface warping of the
optical disk or the like, a scratch on the information

recording surface or the like. Accordingly, it is possible to accurately avoid the collision between the objective lens and the optical disk.

[0028] The use of the disk collision avoiding device is not limited to a CD player or a CD recorder. The disk collision avoiding device can be also applied to a DVD (Digital Video (Versatile) Disk) player, a DVD recorder, a CD drive for a personal computer, a DVD drive for a personal computer or the like.

10 FIRST EMBODIMENT

[0029] Fig. 1 is a schematic of a pickup according to a first embodiment of the present invention. A pickup 10 is moved in a plane direction parallel to an information recording surface of an optical disk 70 (hereinafter, "radial direction"). The pickup 10 irradiates a light beam onto the information recording surface of the optical disk 70, detects a reflected light from the optical disk 70, and reads information recorded on the optical disk 70.

[0030] The pickup 10 includes a focus servo mechanism 30, a signal detecting unit 15 that detects a reflected light from a light beam source (not shown) of the light beam irradiated on the optical disk 70, and a disk collision avoiding device 1. The focus servo mechanism 30 includes an objective lens holder 20 and an objective-lens driving unit 16.

[0031] The objective-lens driving unit 16 includes a

magnet 13, which is a permanent magnet, and a yoke which is not shown. The objective lens holder 20 includes a focus coil 21 and an objective lens 22.

[0032] An electromagnetic force is generated on the
5 focus coil 21 by applying a current to the focus coil 21.
The objective lens holder 20 is moved on the objective-lens driving unit 16 in a light-beam irradiation direction (a direction perpendicular to the surface of the optical disk 70) by an attraction force or a repulsive force between the
10 electromagnetic force^w and the magnet 13.

[0033] The objective lens 22 converges the light beam from the light beam source (not shown) irradiated onto the optical disk 70, and feeds the convergent beam to the optical disk 70. In addition, the objective lens 22 feeds
15 the light beam reflected by the optical disk 70 to the signal detecting unit 15.

[0034] The signal detecting unit 15 includes a light receiving element such as a quadripartite detector (not shown). The light receiving element detects the reflected
20 light of the light beam irradiated onto the optical disk 70 through the objective lens 22 from the optical disk 70.
The signal detecting unit 15 detects a focus error signal or a reproduced signal from the reflected light from the optical disk 70, and supplies the detected focus error
25 signal or reproduced signal to the disk collision avoiding device 1 to be explained later. The optical disk 70 is a

recording medium on and from which a CD player/recorder records and reproduces information. The optical disk 70 is a disk such as CD or a DVD.

[0035] Fig. 2 is a block diagram of the disk collision
5 avoiding device according to the first embodiment of the present invention. The disk collision avoiding device 1, which avoids the collision of the objective lens 22 against the optical disk 70, includes a focus driving unit 31, a drive-current detecting unit 32, a radial-position
10 detecting unit 34, and a focus control unit (collision avoiding unit) 35.

[0036] The focus driving unit 31 is connected to the focus coil 21. The focus driving unit 31 applies a current to the focus coil 21 to drive the objective lens holder 20.
15 The focus driving unit 31 controls a relative position of the objective lens 22 connected to the focus coil 21 to the pickup 10 by controlling an amount of the current (focus drive current) applied to the focus coil 21. Namely, the focus driving unit 31 can control the relative position of
20 the objective lens 22 to the optical disk 70 by controlling the amount of the current applied to the focus coil 21.

[0037] The drive-current detecting unit 32 includes a measuring circuit that measures the amount of the focus drive current (DC component) applied by the focus driving
25 unit 31 to the focus coil 21. The drive-current detecting unit 32 measures the focus drive current applied by the

focus driving unit 31 to the focus coil 21.

[0038] The radial-position detecting unit 34 detects a distance of the objective lens 22 in a radial direction from a center of the information recording surface of the optical disk 70 (hereinafter, "radial distance"). The radial-position detecting unit 34 detects the radial distance of the objective lens 22 to the optical disk 70 based on, for example, address information in the reproduced signal read from the optical disk 70.

10 [0039] The focus control unit 35 includes a threshold calculating unit (an access limit introducing unit) 36 and a storing unit 37. The threshold calculating unit 36 makes the focus drive current and the radial distance of the objective lens 22 in the in-focus state (at a position at which the light beam is in optimum focal point) correspond to each other based on the focus drive current supplied from the drive-current detecting unit 32, the radial distance of the objective lens 22 supplied from the radial-position detecting unit 34, and the focus error signal supplied from the pickup 10.

[0040] The threshold calculating unit 36 makes the drive current and the radial distance of the objective lens 22 in the in-focus state correspond to each other at a plurality of positions (radial distances) of the optical disk 70. The threshold calculating unit 36 calculates at which position on the surface of the optical disk 70 the

objective lens 22 is in the in-focus state with which focus drive current (calculates a warping of (shape information on) the optical disk 70). The threshold calculating unit 36 calculates thresholds of the focus drive current for the
5 objective lens 22 based on the following information:
information at which position the optical disk 70 the objective lens 22 is in the in-focus state with which focus drive current, and the focus drive current (corresponding to the focus drive current Iwd to be explained later)
10 necessary to move the objective lens 22 in the in-focus state to a position at which the objective lens 22 collides against the optical disk 70.

[0041] The threshold calculating unit 36 calculates the thresholds of the focus drive current before a reproducing
15 processing on the optical disk 70. If the focus drive current from the drive-current detecting unit 32 exceeds the corresponding threshold during the reproducing processing on the optical disk 70, the threshold calculating unit 36 transmits, to the focus driving unit 31,
20 information on a command to control the movement of the focus coil 21.

[0042] The storing unit 37 stores therein the focus drive current Iwd necessary to move the objective lens 22 in the in-focus state to the position at which the
25 objective lens 22 collides against the optical disk 70, and the thresholds of the focus drive current calculated before

the reproducing processing on the optical disk 70.

[0043] Operations performed by the respective constituent elements shown in Figs. 1 and 2 will be explained while referring to the flowchart of Fig. 3. The optical disk 70 is inserted into the CD player or the like that includes the disk collision avoiding device 1 (step S100). When the optical disk 70 is inserted into the CD player, the threshold calculating unit 36 starts measuring the warping of the optical disk 70 before the reproducing or recording processing is performed on the optical disk 70.

[0044] The pickup 10 is moved in the plane direction parallel to the surface of the optical disk 70. When the pickup 10 is moved to a predetermined position (a position X1 to be explained later) at which the pickup 10 can read the information recorded on the optical disk 70, the focus control unit 35 transmits, to the focus driving unit 31, information on a command to drive the pickup 10. The focus driving unit 31 that receives the command information from the focus control unit 35 applies the current to the focus coil 21 of the pickup 10. The objective lens holder 20 including the objective lens holder 20 is thereby driven, and the light beam is irradiated onto the optical disk 70 that is being rotated.

[0045] The signal detecting unit 15 extracts the focus error signal from the reflected light from the optical disk 70, and transmits the focus error signal to the threshold

calculating unit 36. Furthermore, the drive-current
detecting unit 32 measures the focus drive current at time
when the signal detecting unit 15 extracts the focus error
signal of zero. The radial-position detecting unit 34
5 acquires the information (the address or the like of the
optical disk 70) on the position at which the signal
detecting unit 15 extracts the focus error signal from the
reflected light (reproduced light) from the optical disk 70.
[0046] At this moment, the optical disk 70 is rotated.
10 By measuring the focus error signal and the focus drive
current for predetermined time at the position at which the
focus error signal is extracted, an average focus error
signal and an average focus drive signal at radial
positions same in distance from the center are obtained.
15 [0047] Fig. 4 is an example of the focus error signal.
In Fig. 4, a horizontal axis indicates the distance
(irradiation direction distance) between the objective lens
22 and the surface (signal surface) of the optical disk 70.
A vertical axis indicates an output of the focus signal.
20 [0048] The output of the focus error signal (focus error
output) is changed to draw an S-curve according to the
distance between the objective lens 22 and the surface of
the optical disk 70. The signal detecting unit 15 included
in the pickup 10 is set so that the focus error signal is
25 equal to zero when the light beam irradiated onto the
optical disk 70 is in optimum focal point (when the

objective lens 22 is in the in-focus state). Therefore, a distance y between the objective lens 22 and the surface of the optical disk 70 when the focus error signal is equal to zero is always a constant value (a distance WD to be
5 explained later).

[0049] Fig. 5 is a schematic for explaining the relationship between the focus drive current and the in-focus state calculated by the disk-collision avoiding device. The pickup 10 reads the information recorded on
10 the optical disk 70 in a state in which the optical disk 70 is rotated. The signal detecting unit 15 detects focus error signals at a plurality of positions X_1 to X_n , respectively, from a closer position (inner position) (X_1) to the center of the surface of the optical disk 70 to a
15 farther position (outer position) (X_n (where n is a natural number)) from the center. The drive-current detecting unit 32 measures focus drive currents I_1 to I_n corresponding to the focus error signal of zero.

[0050] At the position X_n , the objective lens 22 turns
20 into the in-focus state when the objective lens 22 is moved from the objective-lens driving unit 16 (pickup 10) in the light-beam irradiation direction by a distance h_n . The drive current at this time is assumed as the focus drive current I_n . It is also assumed that the distance h_n
25 between the objective-lens driving unit 16 and the objective lens 22 is a distance (distance from the neutral

position) by which the objective lens 22 is moved from the position of the objective lens 22 relative to the objective-lens driving unit 16 when the focus servo control is open (inoperative) to the position in the in-focus state.

5 [0051]

 In the first embodiment, the following instance will be explained. The signal detecting unit 15 detects the focus error signal at the four positions (from the inner position (X1) to the outer position (X4) on the surface of
10 the optical disk 70. The threshold calculating unit 36 measures the drive currents I1 to I4 corresponding to the focus error signal of zero at the respective positions X1 to X4.

[0052] The distance between the objective lens 22 and
15 the surface of the optical disk 70 is changed according to the warping or deflection of the surface of the optical disk 70 or a mechanical dimensional error of an attachment position of a spindle motor (not shown) or the like. For instance, because of a difference in shape among a
20 plurality of optical disks 70, distances h1 to h4 by which the objective lens 22 is moved from the objective-lens driving unit 16 to irradiate the light beam with optimum focal point onto the optical disk 70 at the respective positions X1 to X4 differ among the optical disks 70.

25 Furthermore, because of the warping of the optical disk 70 or the like on the surface of even one optical disk 70, the

distances h1 to h4 differ according to radial positions of the objective lens 22. Due to this, the focus drive currents I1 to I4 for moving the objective lens 22 from the neutral position to the position in the in-focus state
5 differ on the surface of the optical disk 70.

[0053] In the first embodiment, the signal detecting unit 15 detects the focus error signal first at the position X1, and the drive-current detecting unit 32 measures the focus drive current at the position X1. In
10 addition, the radial-position detecting unit 34 acquires information on the position X1 at which the focus error signal is detected, and transmits the information to the focus control unit 35.

[0054] The pickup ^o10 is then moved to the radial
15 position X2 other than the position X1 in the plane direction parallel to the surface of the optical disk 70. At the position X2, similarly to the position X1, the signal detecting unit 15 detects the focus error signal, and the drive-current detecting unit 32 measures the focus
20 drive signal. In addition, the radial-position detecting unit 34 acquires information on the position X2 and transmits the information to the focus control unit 35.

[0055] The pickup 10 is further moved to the other radial positions X3 and X4 in the plane direction in
25 parallel to the surface of the optical disk 70. The signal detecting unit 15 detects the focus error signals at the

positions X3 and X4, respectively. The drive-current
detecting unit 32 detects the focus drive currents at the
positions X3 and X4, respectively. The radial-position
detecting unit 34 acquires information on the respective
5 positions X3 and X4, and transmits the information to the
focus control unit 35.

[0056] The threshold calculating unit 36 makes the focus
drive currents and the radial distances in the in-focus
state (at the positions at which the light beam is with
10 optimum focal point) correspond to each other based on the
focus drive currents transmitted from the drive-current
detecting unit 32, the radial distances of the objective
lens 22 transmitted from the radial-position detecting unit
34, and the focus error signals transmitted from the pickup
15 10. In the first embodiment, the focus drive currents at
which the focus error signal is equal to zero at the
positions X1 to X4 correspond to the focus drive currents
I1 to I4, respectively.

[0057] The storing unit 37 of the focus control unit 35
20 stores therein the focus drive currents I1 to I4 in the in-
focus state at the respective positions X1 to X4 as the
information on the shape (warping) of the optical disk 70
(step S200).

[0058] Fig. 6 is a graph for explaining a method of
25 calculating the thresholds of the focus drive currents.

The distance Wd between the objective lens 22 and the

[0059] As shown in Fig. 6, it is possible to calculate the collision drive currents corresponding to all the radial positions of the objective lens 22 on the optical disk 70 based on the relationship between the collision drive currents ($I_{11}+I_{wd}$) to ($I_{14}+I_{wd}$) and the positions X_1 to X_4 by linear interpolation or the like, respectively.

WASH 1689971.1

[0061] The threshold calculating unit 36 calculates the collision drive currents corresponding to all the respective radial positions of the objective lens 22 on the surface of the optical disk 70 as information on the thresholds of the optical drive currents based on the relationship between the collision drive currents ($I_{11}+I_{wd}$) to ($I_{14}+I_{wd}$) and the positions X_1 to X_4 (step S300). The calculated information on the thresholds of the focus drive currents is stored in the storing unit 37.

10 [0062] Next, the CD drive starts the recording or reproducing processing on the optical disk 70 (step S400). When the pickup 10 is moved to the position at which the reproducing processing or the like is started in the plane direction parallel to the surface of the optical disk 70,

15 the focus control unit 35 transmits, to the focus driving unit 31, the information on the command to drive the pickup 10. The focus driving unit 31 that receives the command information from the focus control unit 35 applies the focus drive current to the focus coil 21 of the pickup 10.

20 The objective lens holder 20 including the objective lens 22 is driven accordingly, and the light beam is irradiated onto the optical disk 70.

[0063] During the recording or reproducing processing on the optical disk 70, the signal detecting unit 15 extracts the reproduced signal from the light beam reflected from the optical disk 70 and transmits the reproduced signal to

the focus control unit 35. At this time, it is unnecessary for the signal detecting unit 15 to extract the focus error signal.

[0064] During the recording or reproducing processing on
5 the optical disk 70, the drive-current detecting unit 32
measures the focus drive current. In addition, the radial-
position detecting unit 34 acquires the information on the
radial position of the objective lens 22 from the
reproduced signal transmitted from the signal detecting
10 unit 15. The focus drive current measured by the drive-
current detecting unit 32 and the information on the radial
position of the objective lens 22 acquired by the radial-
position detecting unit 34 are transmitted to the threshold
calculating unit 36.

15 [0065] The focus control unit 35 transmits the command
information to the focus driving unit 31 based on the
following information: the information on the thresholds of
the focus drive currents stored before the reproducing
processing on the optical disk 70, the focus drive current
20 for the optical disk 70 that current is being measured by
the drive-current detecting unit 32, and the information on
the radial positions of the objective lens 22 acquired by
the radial-position detecting unit 34. In the first
embodiment, if the focus drive current measured by the
25 drive-current detecting unit 32 at each radial position of
the objective lens 22 is close to the collision drive

current stored as the corresponding threshold information
by a predetermined value, the focus control unit 35
transmits, to the focus driving unit 31, information on a
command to move the objective lens 22 to be farther from
5 the optical disk 70 or on a command to stop the movement of
the objective lens 22.

[0066] Upon reception of the command information from
the focus control unit 35, the focus driving unit 31
controls the amount of the current applied to the focus
10 coil 21 based on the information from the focus control
unit 35 to avoid the collision between the objective lens
22 and the optical disk 70.

[0067] When the CD drive finishes the recording or
reproducing processing on the optical disk 70 and the
15 optical disk 70 is discharged from the CD drive, the
threshold information on the drive currents stored in the
threshold calculating unit 36 is deleted (step S500).
Alternatively, after the CD drive finishes the recording or
reproducing processing on the optical disk 70, the
20 threshold information on the drive currents stored in the
threshold calculating unit 36 may be stored in the storing
unit 37 until the optical disk 70 is discharged from the CD
drive. By doing so, if the CD drive is turned on again
after supply of power to the CD drive is stopped, it is
25 unnecessary for the threshold calculating unit 36 to
calculate again the threshold information on the drive

currents. If the CD drive is turned on again after the supply of the power to the CD drive is stopped, the threshold information stored in the storing unit 37 is transmitted to the threshold calculating unit 36. The CD
5 drive performs the recording or reproducing processing on the optical disk 70 based on the threshold information of the threshold calculating unit 36.

[0068] The focus drive currents differ in the distance, by which the objective lens 22 can be moved, according to
10 frequencies. Due to this, if the focus drive currents at different frequencies are used, the focus control unit 35 is configured to include an equalizer or the like that corrects each focus drive current.

[0069] Moreover, in the first embodiment, the focus
15 error signal is detected before the recording or reproducing processing on the optical disk 70 while the focus servo control is closed. Alternatively, the focus error signal can be detected while focus servo control is open. In this alternative, the in-focus state is detected
20 by detecting the focus drive signals detected by the drive-current detecting unit 32 and the zero level of the focus error signal. This can reduce the misdetection of the focus error signal when the warping of the optical disk 70 is detected.

25 [0070] In this manner, according to the first embodiment, the thresholds of the focus drive currents are calculated

before the recording or reproducing processing on the optical disk 70. Therefore, during the recording or reproducing processing on the optical disk 70, the distance between the objective-lens driving unit 16 and the objective lens 22 in the optical axis direction can be calculated by detecting the focus drive current. This makes it possible to estimate the irradiation direction distance of the objective lens 22 to the optical disk 70, and to reduce the misdetection of the irradiation direction distance of the objective lens 22 to the optical disk 70. Therefore, possibility of collision between the objective lens 22 and the optical disk 70 can be accurately estimated and the collision can be avoided. Furthermore, even while the focus servo control is open (inoperative), the collision between the objective lens 22 and the optical disk 70 can be avoided by detecting the focus drive currents.

SECOND EMBODIMENT

[0071] A second embodiment of the present invention will be explained with reference to Figs. 7 and 8. In the second embodiment, a position sensor (distance measuring unit) 45 detects the distance between the objective lens 22 and the objective-lens driving unit 16 in a laser irradiation direction.

[0072] Fig. 7 is a schematic of a pickup according to the second embodiment. Fig. 8 is a block diagram of a disk

collision avoiding device. In Figs. 7 and 8, constituent elements that fulfill the same functions as those of the pickup 10 and the disk collision avoiding device 1 according to the first embodiment shown in Figs. 1 and 2 are denoted by the same reference symbols, and will not be repeatedly explained.

[0073] As shown in Fig. 7, an objective-lens driving unit 46 of the pickup 10 includes the position sensor 45. The position sensor 45 detects the (irradiation direction) position of the objective lens 22 relative to the pickup 10 when the signal detecting unit 15 detects the focus error signal. The position of the objective lens 22 detected by the position sensor 45 is transmitted to a disk collision avoiding device 2 as an electric signal.

15 [0074] As shown in Fig. 8, the disk collision avoiding device 2 includes a moving distance calculating unit (moving distance measuring unit) 42. The moving distance calculating unit 42 calculates the electric signal transmitted from the position sensor 45 as a moving distance of the objective lens 22 relative to the objective-lens driving unit 16 using a measuring circuit which is not shown. The moving distance calculated by the moving distance calculating unit 42 is transmitted to the focus control unit 35.

25 [0075] The threshold calculating unit 36 calculates thresholds of moving amounts of the objective lens 22 used

to control the movement of the objective lens 22 (access distance limits of the objective lens 22 to the optical disk 70) based on the following information: the focus error signals calculated by the ~~focus-calculating~~ signal
5 detecting unit 15, the moving distance of the objective lens 22 relative to the pickup 10 calculated by the moving distance calculating unit 42, and the information on the positions X1 to X4 acquired by the radial-position detecting unit 34.

10 [0076] A procedure for avoiding collision between the objective lens 22 and the optical disk 70 in the second embodiment is the same as that explained in the first embodiment and will not be, therefore, explained. In the second embodiment, a method of calculating thresholds of
15 moving amounts used to control the warping of the optical disk 70 and the movement of the objective lens 22, which method differs from the first embodiment, will be explained.

[0077] Fig. 9 is an explanatory view of the relationship between focus drive currents and in-focus states calculated
20 by the disk-collision avoiding device. The pickup 10 reads the information recorded on the optical disk 70 while the optical disk 70 is rotated. The signal detecting unit 15 detects focus error signals at a plurality of positions X1 to Xn, respectively from the inner position (X1) to the
25 outer position (Xn (where n is a natural number)). The position sensor 45 detects positions of the objective lens

22 relative to the objective-lens driving unit 16. The
moving distance calculating unit 42 calculates distances
between the objective-lens driving unit 16 and the
objective lens 22 at the respective positions detected by
5 the position sensor 45.

[0078] At the position X_n , if the distance between the
objective-lens driving unit 16 and the objective lens 22 is
 W_n , it is assumed that the objective lens 22 is in an in-
focus state. It is also assumed that the distance W_n
10 between the objective-lens driving unit 16 and the
objective lens 22 is a distance (distance from the neutral
position) by which the objective lens 22 is moved from the
position of the objective lens 22 relative to the
objective-lens driving unit 16 when the focus servo control
15 is open (inoperative) to the position in the in-focus state.

[0079] In the second embodiment, the following instance
will be explained. The signal detecting unit 15 detects
the focus error signal at the four positions (from the
inner position (X_1) to the outer position (X_4) in the plane
20 direction parallel to the surface of the optical disk 70.
The moving distance calculating unit 42 calculates
distances W_1 to W_4 between the objective-lens driving unit
16 and the objective lens 22 corresponding to the focus
error signal of zero at the respective positions X_1 to X_4 .

25 [0080] Because of a difference in shape among a
plurality of optical disks 70, distances by which the

objective lens 22 is moved from the objective-lens driving unit 16 to irradiate the light beam with optimum focal point onto the optical disk 70 at the respective positions X1 to X4 differ among the optical disks 70. Furthermore, 5 because of the warping or the like of the optical disk 70 on the surface of even one optical disk 70, the distances differ according to the radial positions of the objective lens 22.

[0081] In the second embodiment, the signal detecting 10 unit 15 detects the focus error signal first at the position X1, and the moving distance calculating unit 42 calculates the distance between the objective-lens driving unit 16 and the objective lens 22 at the position X1. In addition, the radial-position detecting unit 34 acquires 15 the information on the position X1 at which the focus error signal is detected, and transmits the information to the focus control unit 35.

[0082] The pickup 10 is then moved to the radial position X2 other than the position X1 in the plane 20 direction parallel to the surface of the optical disk 70. At the position X2, similarly to the position X1, the signal detecting unit 15 detects the focus error signal, and the moving distance calculating unit 42 calculates the distance between the objective-lens driving unit 16 and the 25 objective lens 22. In addition, the radial-position detecting unit 34 acquires information on the position X2

and transmits the information to the focus control unit 35.

[0083] The pickup 10 is further moved to the other radial positions X3 and X4 in the plane direction parallel to the surface of the optical disk 70. The signal
5 detecting unit 15 detects the focus error signal at the positions X3 and X4, respectively. The moving distance calculating unit 42 calculates the distances between the objective-lens driving unit 16 and the objective lens 22 at the respective positions X3 and X4. The radial-position
10 detecting unit 34 acquires information on the respective positions X3 and X4, and transmits the information to the focus control unit 35. At the positions X1 to X4, the distances between the pickup 10 and the objective lens 22 when the focus error signal is equal to zero correspond to
15 the distances W1 to W4 between the objective-lens driving unit 16 and the objective lens 22, respectively.

[0084] The storing unit 37 of the focus control unit 35 stores therein the distances W1 to W4 between the objective-lens driving unit 16 and the objective lens 22 in
20 the in-focus state at the respective positions X1 to X4 as the information on the shape (warping) of the optical disk 70.

[0085] A distance WD between the objective lens 22 and the surface of the optical disk 70 when the focus error
25 output is equal to zero (in the in-focus state) is calculated. By doing so, the distances between the

objective-lens driving unit 16 and the objective lens 22
(hereinafter, "collision moving distances") ($W1+WD$) to
($W4+WD$) if the objective lens 22 collides against the
surface of the optical disk 70 at the positions X1 to X4
5 can be calculated, respectively.

[0086] This makes it possible to calculate the collision
moving distances corresponding to all the radial positions
of the optical disks 70 by the linear interpolation or the
like based on the relationship between the collision moving
10 distances ($W1+WD$) to ($W4+WD$) and the positions X1 to X4,
respectively.

[0087] The threshold calculating unit 36 calculates the
collision moving distances corresponding to all the radial
positions on the surface of the optical disk 70 based on
15 the relationship between the collision moving distances
($W1+WD$) to ($W4+WD$) and the positions X1 to X4, respectively
as information on thresholds of the distances between the
objective-lens driving unit 16 and the objective lens 22.
The threshold calculating unit 36 stores the calculated
20 threshold information in the storing unit 37.

[0088] Subsequently, similarly to the first embodiment,
the focus control unit 35 transmits, to the focus driving
unit 31, information on a command to avoid the collision
between the objective lens 22 and the optical disk 70 if
25 the moving amount of the objective lens 22 calculated by
the moving distance calculating unit 42 exceeds the

threshold of the moving distance calculated in advance
during the reproducing processing on the optical disk 70.
The focus driving unit 31 applies a predetermined current
to the focus coil 21 in response to the command information
5 from the focus control unit 35. In addition, the focus
driving unit 31 controls the position of the objective lens
22 to avoid the collision between the objective lens 22 and
the optical disk 70.

[0089] In this manner, according to the second
10 embodiment, the thresholds of the focal direction distances
between the objective-lens driving unit 16 and the
objective lens 22 are calculated before the recording or
reproducing processing on the optical disk 70. Therefore,
during the recording or reproducing processing on the
15 optical disk 70, the irradiation direction distance of the
objective lens 22 to the optical disk 70 can be calculated
by detecting the distance between the objective-lens
driving unit 16 and the objective lens 22. This makes it
possible to reduce misdetection of the irradiation
20 direction distance of the objective lens 22 to the optical
disk 70. Therefore, the collision between the objective
lens 22 and the optical disk 70 can be accurately estimated
and the collision can be avoided. Furthermore, even while
the focus servo control is open (inoperative), the
25 collision between the objective lens 22 and the optical
disk 70 can be avoided by detecting the focal direction

distance of the objective lens 22 relative to the optical disk 70.

THIRD EMBODIMENT

[0090] A third embodiment of the present invention will be explained with reference to Figs. 10 and 11. In the third embodiment, a position of a movable mechanical stopper is controlled to avoid the collision between the objective lens 22 and the optical disk 70. Fig. 10 is a schematic of a pickup according to the third embodiment. Fig. 11 is a block diagram of a disk collision avoiding device. In Figs. 10 and 11, constituent elements that perform the same functions as those of the pickup 10 according to the first embodiment shown in Fig. 1 and the disk collision avoiding device according to the first embodiment shown in Fig. 2 are denoted by the same reference symbols, and will not be repeatedly explained.

[0091] As shown in Fig. 10, the objective-lens driving unit 46 of the pickup 10 includes a mechanical stopper (movable stopper) 55. The mechanical stopper (movable stopper) 55 includes a magnet 56, a coil 57, and a stopper unit 58. The stopper unit 58 of the mechanical stopper 55 stops the movement of the objective lens 22 to prevent the objective lens 22 from being moved by a distance larger than a predetermined distance relative to the pickup 10.

An electromagnetic force is generated on the coil 57 of the mechanical stopper 55 by causing the focus control unit 35

5 electromagnetic force and the coil 57.

10 57 of the mechanical stopper 55, the mechanical stopper
driving unit 59 drive-controls movement of the stopper unit
58 relative to the pickup 10.

position at which the objective lens 22 does not collide with the optical disk 70. The mechanical stopper driving unit 59 controls the position of the stopper unit 58 by controlling the current applied to the coil 57, and avoids the collision between the objective lens 22 and the optical disk 70. For instance, if a focus drive current I_z calculated by the drive-current detecting unit 32 exceeds

the collision drive current ($I_{l+I_{wd}}$) calculated in advance at the position X_1 during the reproducing processing on the optical disk 70, the mechanical stopper driving unit 59 moves the stopper unit 58 to a position at which the
5 objective lens 22 is moved from the position in the in-focus state to a position at which a moving distance of the objective lens 22 does not exceed the distance WD in a direction of the optical disk 70.

[0094] By doing so, even if the focus drive current
10 detected by the drive-current detecting unit 32 exceeds the threshold of the corresponding focus drive current calculated in advance during the reproducing processing on the optical disk 70, the objective lens 22 collides only against the stopper unit 58. The collision between the
15 objective lens 22 and the optical disk 70 can be, therefore, avoided. Alternatively, the pickup 10 according to the second embodiment may include the mechanical stopper 55, and the disk collision avoiding device 3 2 may include the mechanical stopper driving unit 59.

20 [0095] In this manner, according to the third embodiment, even if the focus drive current exceeds the threshold of the corresponding focus drive current calculated in advance during the reproducing processing on the optical disk 70, the position of the stopper unit 58 in the irradiation
25 direction is controlled. Therefore, the objective lens holder 20 or the like collides only against the stopper

unit 58, and it is possible to ensure avoiding the collision of the objective lens 22 against the optical disk 70.